



**V.S. WATERTREATMENT
MANAGEMENT CO.**

www.vswmco.com

Regd. Office.
Roop Darshan A/21, Juhu Lane, Andheri(W), Mumbai India

Factory.
Plot No 639,100 Shed Area, GIDC, Vapi, India.

sales@vswmco.com

VS CLT 60

CORROSION CONTROL FOR JACKET WATER
SYSTEM

WATERTREATMENT
COOLING TOWER

Description

This product is based on Polymer with nitrite as corrosion inhibitor, this product is dosed in Radiator cooling system prevent scale & corrosion.

Specification

pH	Alkaline 9 +/- 1
Specific gravity	1.1 +/- 0.05
Base	Polymer
Colour	Light pink/green

Advantages

- Prevents scale & Corrosion in the cooling system
- Keeps the metal surface clean so that the scale & Corrosion inhibitors can perform in peak condition.
- Prevents overheating of engine.
- Prevents the Lubrication failure.
- Prevents damages to engine (like cracking of heads etc)

Chemical Dosing

This product is dosed @ 1000 PPM to 4000 PPM based on the make up water added

The dosing will be 1 to 4 liters for 1000 liters of make up fresh water. This chemical is directly dosed in the radiator. A light pink is maintained in the Radiator cooling system.

After dosing VS-CLT-60 it should be ensured that the radiator lid is closed properly.

Handling

In Case of eye contact wash eyes with running water immediately and give medical attention, if required.

Packing

25/35/50 liters HDPE carboys